

VEXTROM ULTIMATE GEAR OIL FULL SYNTHETIC SAE 75W-90

A breakthrough gear oil technology that combines 100% synthetic base oil with a selected additive system that includes extreme-pressure and limited-slip additives, and an improved viscosity modifier to provide maximum protection, longer gear life and an outstanding power transfer performance.

- Exceptional thermal and shear stability for superior viscosity and wear protection.
- Superior resistance to high temperature foaming and oxidation.
- Excellent protection under high speed, high torque and high horse-power conditions.
- Extends drain intervals.
- Improve fuel economy.
- Outstanding low temperature start-up protection.
- Recommended for use in manual transmissions (conventional and limited slip) of modern high performance automobiles, trucks and off-highway vehicles, under severe service conditions.
- Extra protection with Xpand-Life Technology.

Specification & Approvals:

API GL-5, GL-4, GL-2/3, GL-1 MT-1; MIL-PRF-2105E; SAE J-2360: Dana Corp. (including Eaton Axles); Eaton 750,000 mile warranty coverage and 500,000 mile oil drain intervals capabilities; General Electric D 50E9C; (P&H) 474; Mack GO-J Plus; ArvinMeritor (including former Rockwell axels) and Rockwell International O-76-E; Limited Slip: M2C119A, M2C154A; Outboards and Stern Drives.

ULTIMATE GEAR OIL FULL SYNTHETIC	SAE 75W-90
API	GL-5
API Gravity	27.5
Flash Point C°	210
Viscosity, cSt @100 C°	17
Viscosity, cSt @40 C°	130
Viscosity Index	142
Pour Point C°	-45