

## TRANSMISSION MAX GL-4

Gear lubricant formulated with Extreme Pressure (EP) additives for manual transmissions, differentials and gears. Suitable for all cars, trucks and other medium duty equipment gears requiring API Service GL-4 and operating at high speed low torque or low speed high torque. Transmission Max GL-4 offers thermal stability and resistance to degradation and soot deposits.

### Benefits:

- Gears protection.
- Thermal stability
- Oxidation and wear resistance to help extend gear component's life.

It meets API service classifications GL-4 / MT-1, Mack GO-J Plus and MIL-L-2105 E (MIL-PRF-2105E).

TRANSMISSION MAX GL-4				
ISO Grade	90	140	80W - 90	85W - 140
AGMA Grade	> 5 EP	8 EP	> 5 EP	8 EP
Flash Point, COC, °F (°C)	470 (245)	475 (246)	470 (245)	475 (246)
Pour Point, °F (°C)	10 (-12)	12 (-10)	10 (-12)	12 (-10)
Specific Gravity, 60/60 °F	0.9273	0.9279	0.9273	0.9279
API Gravity @ 60 °F	21.10	21.00	24.50	24.00
Viscosity Index	31.00	38.00	95.00	95.00
Viscosity, cSt @ 40 C°	237.50	373.58	143.00	360.00
Viscosity, cSt @ 100 C°	14.50	19.43	14.00	26.00
Viscosity, SUS @ 100 °F	1288.00	2044.00	720.00	1800.00
Viscosity, SUS @ 210 °F	78.00	99.10	72.00	125.00

